



**Product Data Sheet:**

# ANTIFREEZE G 12 PLUS

## Product Description:

**ANTIFREEZE G 12 PLUS** is the latest generation silicate free antifreeze and is because of its high-grade quality already used as a first fill by more than 75% of automobile manufacturers. **ANTIFREEZE G 12 PLUS** is developed partly due to the demand of a full organic antifreeze. Before use, this special antifreeze needs to be diluted in the recommended proportions.

**ANTIFREEZE G 12 PLUS** is a silicate free antifreeze, based on mono ethylene glycol under addition of special additives to obtain the following properties:

- Extremely powerful organic corrosion inhibitors resulting in an extended life-time of the radiator, pump and pipes.
- A strong protection: up to 650.000km for busses and trucks, 250.000km for passenger vehicles and up to 16.000 for steady-state engines. It is recommended to change the coolant every five years or at above mileages or operating times, whichever comes first.
- High Boiling Point, which decreases the risk of overheating of the antifreeze. During hot summers of heavy duty operating circumstances the antifreeze offers extra protection.
- A strong compatibility seals: completely compatible with elastomers used by European constructors.
- Excellent stability with hard water, because this antifreeze doesn't contain silicates nor other mineral salts. **ANTIFREEZE G 12 PLUS** prevents the formation of deposits and scale and is perfectly mixable with other antifreezes based on mono ethylene glycol.

## **WARNING:**

**Keep all anti freezes out of reach of children! Do not drink antifreeze!**

**If swallowed, induce vomiting and immediately call for a doctor!**

**See also Safety Data Sheet of this product!**

## **Specifications:**

**Exceeds:** VW TL-774D/F (G12+), MB 325.3, FORD ESE-M97B49-4/44C, FORD WSS-M97B44-D, MAN 248 & 324 SNF, GM/OPEL 1940656/6277M, SCANIA, Volvo no: 260, Renault: 41-01-001, PSA B715110

<b>Property:</b>	<b>Test Method:</b>	<b>Typical Values:</b>
Colour	-	Red
Density @ 15°C	ASTM D1298	1120 kg/m <sup>3</sup>
Freezing point @ 40% in water	ASTM D1177	-27°C
Freezing point @ 50% in water	ASTM D1177	-40°C
pH (50% in water)	ASTM D1287	7.6

Product nr: 4385

Date Issued: 04/11/2011

Date Superseded: 23/07/2010

Revision nr: 02