



Product Data Sheet

MOTOR OIL CP 0W-30

Product Description:

MOTOR OIL CP 0W-30 is a high performance fuel saving engine oil based on 100% synthetic technology to be used in gasoline- and diesel engines of the latest generation passenger cars and light vans where a ACEA C2 specification is required and suitable for all engines which require an PSA B71 2290 performance specification.

MOTOR OIL CP 0W-30 is based on high performance 100% synthetic technology oil in combination with a specially selected additive technology to ensure the following properties:

- Excellent thermal and oxidation stability.
- Fuel saving properties.
- Excellent protection against wear, foam and corrosion.
- Low temperature properties, to ensure a smooth cold start.
- Long oil drain interval possible.

MOTOR OIL CP 0W-30 exceeds the following performance criteria:

ACEA C2 PSA B71 2290 Ford M2C950-A

| Properties | Unit | Test Method | Typical Value |
|---------------------------|--------------------|-------------|---------------|
| SAE Grade | | SAE J3000 | 0W-30 |
| Density@15°C | kg/m ³ | ASTM D4052 | 843 |
| Kin. Viscosity @40°C | mm ² /s | ASTM D7042 | 47 |
| Kin. Viscosity @100°C | mm ² /s | ASTM D7042 | 9.7 |
| Viscosity Index | | ASTM D2270 | 200 |
| Viscosity CCS @-30°C, max | cP | ASTM D2270 | 6200 |
| Flash Point COC | °C | ASTM D92 | >201 |
| Pour Point | °C | ASTM D7346 | -45 |
| Total Base Number | mgKOH/g | ASTM D2896 | 7.9 |
| Sulphated Ash | %Wt | ASTM D874 | 0.79 |

Product Nr: 4243

Date Issued: 16-01-2018

Date Superseded: 26-08-2016

Revision nr: 03